



Lead Free Pewter
EU Nickel Compliant
Made in the USA
Original Designs

Supplies

- | | |
|--------------------------------------|------------------------------------|
| 1 Classic Hook (94-6178-40) | 8 7mm Spacer Beads
(93-0450-40) |
| 2 3 Hole Bars (94-3162-40) | |
| 2 6x2mm Barrel Beads
(94-5792-40) | 28" 2mm round leather cord |
| 7 4x2mm Barrel Beads
(94-5791-40) | |

Required Tools

Flat nose pliers, scissors, jewelry
adhesive

Finished Size

8" bracelet

Lazy Zigzag Bracelet

A Meandering Weave of Cord and Beads

DESIGN BY Tracy Gonzales (for TierraCast®)

Instructions

TIP: For added security, apply adhesive into the barrel beads before crimping, and to knots before tightening and trimming.

1. Cut one 14" and two 6 1/4" pieces of cord.
2. Align cords next to each other with 14" strand in middle extending 4" past ends of outer cords.
3. String one 6x2mm barrel bead onto all three cords and position at ends of outer cords.
4. Secure in place by crimping with flat nose pliers.
5. Trim ends of outer cords flush with bead.
6. Thread small end of Classic Hook onto 4" end of center cord.
7. Fold cord over to form a small loop near bead.
8. Grasp loop with one hand. With other hand wrap loose end of cord around base of loop once. Tuck loose end through wrap to form overhand knot. (Fig.1)
9. Tighten securely. Trim excess cord.
10. String one 3 hole bar onto the three cords.
11. String one 7mm spacer bead onto center cord. String one 4x2mm barrel bead onto center and one outer cord.
12. Repeat Step 11 six times, alternating outer cords.
13. String final nugget bead onto center cord, then second 3 hole bar.
14. Adjust all beads so that 3 hole bars are 5" apart (less for smaller bracelet).
15. Repeat Steps 3-5, adjusting position of barrel bead as necessary.
16. Repeat Steps 7-9, adjusting size of loop as desired.



Fig 1

